



PJX8808

20V N-Channel Enhancement Mode MOSFET


Voltage 20 V **Current** 500mA

Features

- Low Voltage Drive (1.2V).
- Advanced Trench Process Technology
- Specially Designed for Switch Load, PWM Application, etc.
- ESD Protected
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : SOT-563 Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.0026 grams
- Marking : X08



Maximum Ratings and Thermal Characteristics (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNITS
Drain-Source Voltage	V _{DS}	20	V
Gate-Source Voltage	V _{GS}	±10	V
Continuous Drain Current	I _D	500	mA
Pulsed Drain Current	I _{DM}	1000	mA
Power Dissipation	PD	T _A =25°C	300
		Derate above 25°C	2.8
Operating Junction and Storage Temperature Range	T _J , T _{STG}	-55~150	°C
Typical Thermal Resistance	R _{θJA}	417	°C/W
- Junction to Ambient ^(Note 3)			



PJX8808

Electrical Characteristics (T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Static						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	20	-	-	V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250uA	0.3	0.64	0.9	V
Drain-Source On-State Resistance	R _{DS(on)}	V _{GS} =4.5V, I _D =500mA	-	310	400	mΩ
		V _{GS} =2.5V, I _D =200mA	-	360	650	
		V _{GS} =1.8V, I _D =100mA	-	430	800	
		V _{GS} =1.5V, I _D =50mA	-	510	1200	
		V _{GS} =1.2V, I _D =20mA	-	710	3000	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =16V, V _{GS} =0V	-	-	1	uA
Gate-Source Leakage Current	I _{GSS}	V _{GS} =±8V, V _{DS} =0V	-	±0.5	±10	uA
Dynamic ^(Note 5)						
Total Gate Charge	Q _g	V _{DS} =10V, I _D =500mA, V _{GS} =4.5V ^(Note 1,2)	-	1.4	-	nC
Gate-Source Charge	Q _{gs}		-	0.22	-	
Gate-Drain Charge	Q _{gd}		-	0.21	-	
Input Capacitance	C _{iss}	V _{DS} =10V, V _{GS} =0V, f=1.0MHZ	-	67	-	pF
Output Capacitance	C _{oss}		-	19	-	
Reverse Transfer Capacitance	C _{rss}		-	6	-	
Turn-On Delay Time	t _{d(on)}	V _{DD} =10V, I _D =150mA, V _{GS} =4.0V, R _G =10Ω ^(Note 1,2)	-	2.8	-	ns
Turn-On Rise Time	t _r		-	20	-	
Turn-Off Delay Time	t _{d(off)}		-	23	-	
Turn-Off Fall Time	t _f		-	23	-	
Drain-Source Diode						
Maximum Continuous Drain-Source Diode Forward Current	I _s	---	-	-	500	mA
Diode Forward Voltage	V _{SD}	I _s =500mA, V _{GS} =0V	-	0.87	1.3	V

NOTES :

1. Pulse width ≤ 300us, Duty cycle ≤ 2%
2. Essentially independent of operating temperature typical characteristics.
3. R_{θJA} is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins mounted on a 1 inch FR-4 with 2oz. square pad of copper.
4. The maximum current rating is package limited.
5. Guaranteed by design, not subject to production testing.



PJX8808

TYPICAL CHARACTERISTIC CURVES




Fig.1 On-Region Characteristics




Fig.2 Transfer Characteristics




Fig.3 On-Resistance vs. Drain Current




Fig.4 On-Resistance vs. Junction temperature




Fig.5 On-Resistance Variation with VGS.




Fig.6 Body Diode Characteristics



PJX8808

TYPICAL CHARACTERISTIC CURVES




Fig.7 Gate-Charge Characteristics




Fig.8 Breakdown Voltage Variation vs. Temperature




Fig.9 Threshold Voltage Variation with Temperature




PJX8808

Part No. Packing Code Version

Part No. Packing Code	Package Type	Packing Type	Marking	Version
PJX8808_R1_00001	SOT-563	4K pcs / 7" reel	X08	Halogen free RoHS compliant
PJX8808_R2_00001	SOT-563	10K pcs / 13" reel	X08	Halogen free RoHS compliant

Mounting Pad Layout





PJX8808

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.